

### Smart Single Surface Socket Relay

Product Code:  
**KBSKTR2400**

#### APP Installation

Visit [www.kasta.com.au](http://www.kasta.com.au) or your app store to download the free KASTA app.  
iOS: requires iOS 9.0 or later.  
Android: requires Android 4.4 or later.  
Devices must support Bluetooth 4.0



#### Important Safety Information

- This product must be installed by a licensed electrician in accordance with all the requirements of AS/NZS 3000 (current edition) and other relevant Standards and Regulations.
- Electricity MUST be disconnected prior to installation. Failure to do so may result in serious injury and or loss of life.
- Indoor use only. Not suitable for damp or explosive environments.
- Complies to Australian Standards AS/NZS 60950.1:2015, AS/NZS CISPR 15.
- No user serviceable parts inside.

#### FEATURES

- Suit loads with a standard 2 or 3-pin plug.
- Load control button and LED status indicator.
- Rear load output terminal for wiring to additional traditional surface sockets downstream in the circuit (up to maximum load rating of the KASTA surface socket relay).
- Simple 5 wire connection – N, E, Load, Loop.
- Pair with KASTA remote switch devices for control (up to 8x maximum).
- Smart functions programmed via phone/tablet with the KASTA app. This includes schedules, timers, scenes and groups.
- Built in overvoltage and overcurrent protection.
- Patent No. 2020100101, 201921829033.1.

#### FUNCTION SETUP

Operate via Load Control Button.

ON/OFF SWITCH	1 CLICK
Turns lights on or off.	
DELAY TO OFF	3 CLICKS*
Lights automatically turns off after set time selected via the app. Status Indicator will flash 3 times if successful. 1 click to cancel, Status Indicator will flash once.	
FACTORY RESET	9 CLICKS

Restores all settings back to factory.

\*If successful, light will pulse the number of times that the switch was clicked, indicating function.

#### TECHNICAL SPECIFICATIONS

**Operating Temp:** -20°C to 40°C

**Supply:** 220-240V AC 50Hz

**Load Wattage:** 2400W, 10A, M.40

**Standby:** <1W

**LED:** Max. Load 1200W


**Electronic step-down converter:** Max. Load 1200W

**Ceiling Exhaust Fan:** Max. 100W


**Thermal Derating:** 40°C - 60°C (350W-250W)

#### CONNECTION DIAGRAM

**INDIVIDUAL LOAD1**  
SMART SINGLE SURFACE SOCKET DIMMER  
KBSKTD350



**INDIVIDUAL WITH ADDITIONAL SOCKET**  
SMART SINGLE SURFACE SOCKET DIMMER  
KBSKTD350



**INDIVIDUAL WITH MULTIPLE SOCKETS**  
SMART SINGLE SURFACE SOCKET DIMMER  
KBSKTD350

