

Switch Relay Mechanism

KASTA-RM1440BH-W




Smart push button switch relay mechanism that clips into standard wall plate

FEATURES

- Max. load 1440W or 100W motor
- Slim design allows installation up to 6 onto a standard wall plate
- Reliable Bluetooth® mesh network connectivity to all your KASTA devices
- 8-way multiway control
- Short press for ON/OFF control
- Over-current protection
- Supports core KASTA functionality - control devices, groups, scenes, timers and scheduling
- Suits most Australian wall plates
- Supplied with White button caps (2 x styles)
- iOS and Android app setup and control
- 3 year warranty

CONNECTION



SPECIFICATIONS

Power Supply	220-240V a.c. 50Hz
Operating Ambient Temperature	-20 to 40°C
IP Rating	IP20
Thermal Derating	25 to 40°C (1440W-475W)
Physical Connection Type	Fly leads
Wiring Connections	Active, Load & Neutral
LED Load Wattage	15W - 1440W*, M.5
Multi-gang Derating	2-1300W, 3-1150W, 4-950W, 5-720W, 6-475W @ 25°C
Housing Material	Polycarbonate (PC)
LED Indicators	Blue
Standards Complied	CoS SAA 183650, AS/NZS 60669.2.1, AS/NZS 60669.1, AS/NZS CISPR 15, AS/NZS 4268

*May require load correct capacitor if less than 15W (supplied in box). Suitable for use with small fan motors <100W (0.5A @ 0.8pF).

DIMENSIONS

