





Switch Relay Module

KASTA-S2400IBH Bluetooth Switch Relay

Smart Wireless Switch Relay that fits in behind a standard wall plate and connects to a momentary button. It can be manually operated, and controlled via the free KASTA app or programmed for automated operation.

Applications
Residential dwellings, Apartments, Commercial, Retail, Hospitality, Accommodation, New construction, Retrofit & Renovation

Download the KASTA app




FEATURES

- Mains powered switch relay
- 3 wire connection for power and load, with 2 wire connection for momentary push button mechanism
- Short press for on/off control
- Wireless Bluetooth Mesh communication
- Can be paired with KASTA remote switches for multi-way control
- Configured and controlled using the KASTA app (iOS and Android)
- Group and Scene functions
- Timer and Scheduling functions
- Suits all Australian wall plates using a momentary mechanism
- 3 year warranty


ELECTRICAL

Power Supply	220-240VAC 50Hz
Physical Connection Type	Terminals
Wiring Connections	Active, Neutral, Load & Momentary Mechanism
Momentary Input (T1/T2)	Local signal input only (not 240VAC)
LED Load Power	2W to 2400W
Operating Ambient Temperature	-20 to 40°C
Thermal Derating	25 to 40°C (2400W-1200W)
Wireless Range	Up to 30m open air Up to 20m (typical indoors, depending on building materials)
Form Factor	Module (puck)
Housing Material	Polycarbonate (PC)
Multi-gang Derating	2=1800W, 3=1320W @25°C
Standards Complied	CoS SAA 183649 AS/NZS 60669.2.1 AS/NZS 60669.1 AS/NZS 4268 AS/NZS CISPR15

CONNECTION DIAGRAM



DIMENSIONS



* Maximum 8 Remote Switches

Specification subject to change without prior notice. Last updated 22/07/2020

kasta.com.au